power 2GO

PT-200H

A New Remote Lighting Experience:
Illuminate Your Space at Will

Portable Pan-tilt Light

STABLE, EFFICIENT, AND MORE CONVENIENT TO USE.

Expanding or requires just two steps and can be completed in 10 seconds.

1 Release the legs

2 Release and rise the extension pole

Secure the light at any height with the buckle.

One-click release or lock of the legs.

Ground pegs are available to secure the light tower, providing wind and vibration resistance. (Optional)



HUMANIZED DESIGN HIDDEN IN THE DETAILS

30 Meters Remote Range

Remote control for adjusting the light head.

Phone Stand

Continue working while charging, the hook here can serve as a phone stand.



Car Charger

Use the CC-3 car charger to charge the PT-200H in the car.



REMOTE CONTROL DESIGN FOR INCREASED WORK EFFICIENCY.

360-DEGREE
HORIZONTAL ROTATION

Rotate freely in 360 degrees horizontal direction, instantly rotate/stop with remote commands.

180-DEGREE
VERTICAL ROTATION

Rotates up to 180 degrees up and down, precisely pointing to any target position.

LOWER CENTER OF GRAVITY GREATER STABILITY.

Ultra-low center of gravity combined with extended legs effortlessly handles strong winds and slopes.

ULTRA-LONG WORKING HOURS

Standard Mode Up To **8+** Hours

D24-100 x 2

3 Levels of Brightness （D24-100x2）

Eco	Standard	Turbo
38h	8.7h	5h

Battery compartment fits
two replaceable battery packs.

HIGH LIGHT EFFICIENCY ILLUMINATING A WIDER SPACE

Equipped with high-brightness LED light source and high-quality optical lens system

Three lighting modes to choose from

Distance Mode

Midrange Mode

Close-range Mode

Battery-powered Up To

12,000 LM

Battery (3 Mode)	
Eco	12,00LM
Standard	6,500LM
Turbo	12,000LM

MULTI-DEVICE NETWORK NO SHADOWS!

Multiple units can be controlled with single operator, offering shadow-free illumination and adjustable angles for different work areas.

Long distance

Ultra-high brightness focused lighting.



Medium distance

Balancing illumination distance and brightness.

Short distance

Wide-area lighting coverage.



Construction

Emergency

Military

Railway

Mining



Highway

Heavy lifting

Electric power

Designed for single-person operation

Easy to grip and move,

weight **9.7 kg** excluding battery pack.

Specifications

PT-200H

Height	1.44~2.3m
Weight	9.7KG (Fitting only)
Power Supply	D24 series battery pack
Lumens	0-12000Lm
Run Times	>8.7h (D24-100 x 2)
IP Grade	IP66
Output(USB)	5V 2A
Operating Temp	-10℃~50℃

Size (mm)



Package

Model	PT-200H
Size of Carton	1550x270x360mm
Gross Weight of Carton	13KG
PCS/Carton	1